



ESCAPE **BIVVY INSTRUCTIONS**

XF2 & XF2 COMPACT

XF2 Assembly:

1. Using the point of the V in the folded groundsheet as a guide to where the door will be, place the folded Escape XF2 into position and peg the two rear corners into place. Carefully open the outer arms.
2. Standing in front of the doorway and holding the front crossbar, pull the Escape XF2 upwards and towards you to raise the bivvy into position. Stand inside the bivvy and lock the two internal X-Frame bosses into place by sliding them upwards along the internal side bars until firmly seated in the location point.
3. Clip the two short non-adjustable tension bars into their corresponding position to extend the front peak. Clip the long curved non-adjustable tension bar across the two shorter bars to ensure no rainwater can pool in the peak area.
4. Peg the perimeter of the bivvy to the ground and zip on the flysheet if required (see fitting instructions).
5. Clip the four adjustable tension bars between the rear bars of the inner X-Frame. These only require light pressure to operate effectively, DO NOT over-extend.

XF2 Disassembly:

1. Remove flysheet, all tension bars and all perimeter pegs except the two rear corners.
2. Firmly depress the two X-Frame locking bosses downward along the side bars to unseat them and release tension from the canopy. Holding the front crossbar of the Escape XF2, carefully lower the bivvy to the floor ensuring all material is folded neatly between the crossbars.
3. With the Escape XF2 now completely on the floor and starting with arm #1, carefully fold the outer arms inwards until they meet the crossbars ensuring the groundsheet folds neatly into a V-shape. Unpeg the two rear corners.
4. Ensuring all material is folded neatly, roll the frame forwards to gather up any excess groundsheet. Your Escape XF2 can now be placed inside the carry bag until your next session*

***Note:** see storage information

Flysheet:

1. Zip the flysheet to the corresponding zip on the rear of the Escape XF2, assemble the elasticated curved flysheet support bar and attach it to the inside of the flysheet using the velcro tabs sewn into the flysheet material.
2. Screw the supplied storm poles onto each end of the curved flysheet bar, locate the upright storm poles in the velcro retaining flaps of the Escape XF2 and attach the flysheet hooks to the retaining rings on the storm poles.
3. Adjust the height of the storm poles and peg the flysheet to the ground at the rear of the Escape XF2, ensuring a generous gap between flysheet and bivvy for optimum protection.
4. Removal is a reverse of fitting.

Storage & Aftercare:

Proper storage is one of the most vitally important aspects of caring for your new XF2 Bivvy and every effort should be taken to ensure the bivvy is packed away dry. If you need to pack away the bivvy when it is wet, it is of paramount importance that it is unpacked and dried within 24 hours before being repacked dry. If stored when damp or wet mildew and rust will be able to form, both of which can severely damage the product and its accessories.

Always store in a cool, dark, dry place away from sources of heat or moisture. If storing for extended periods, we recommend unzipping the carry bag to allow fresh dry air to circulate.

Regularly cleaning and reproofing your XF2 bivvy will maintain its ability to repel water. Use only clean, fresh water and a soft brush or cloth to clean your XF2 bivvy. Do not use detergents or chemicals of any sort and never machine wash or tumble dry your bivvy

Warranty:

RidgeMonkey provides customers with a comprehensive warranty of two years from the date of purchase. Please keep your receipt in a safe place as it may be needed in the event of a claim. Your warranty covers replacement or repair at our discretion in the event of a manufacturing fault. Cover excludes damage arising from (but not limited to) misuse, neglect, improper storage, improper cleaning, Acts of God and cover is valid when your product is being used for recreational purposes only. No consequential loss may be claimed. This warranty is provided in addition to your statutory rights in the country of purchase.

Warning:

- **NEVER** use any fuel-burning products inside or within close proximity of your Escape XF2 bivvy. Doing so can result in the accumulation of dangerous concentrations of carbon monoxide which can be fatal.
- While the Escape XF2 is built using CPAI-84 flame resistant fabric, it is not fireproof and will burn if left in continuous contact with an open flame or other heat source. Failure to keep flame and heat sources away from the Escape XF2 can lead to fire which may result in serious injury or death.
- Always peg down your Escape XF2 properly to reduce the risk of loss or injury. Enough pegs and guy ropes are supplied to safely secure your Escape XF2 in most situations, however it may be necessary to purchase additional pegs and ropes for use in extreme conditions. Tightly tensioning your Escape XF2 with the included guy ropes further increases its strength and stability and we recommend that you do so whenever possible.
- Always maintain adequate ventilation inside your Escape XF2 at all times to help reduce the build-up of condensation, moisture and odour. Use of the flysheet will also help to maintain temperature and prevent the build-up of condensation inside the Escape XF2.

Contact Us:

For any enquiries or comments concerning our products, please use the contact form on www.ridgemonkey.co.uk or call our dedicated Customer Services team on **+44 151 486 7070**, and we will respond to you as soon as possible.

Statement:

- In the first instance, we're only able to provide after-sales service for purchases made directly from RidgeMonkey. If you purchased your product through an authorised retailer, please contact them for any warranty issues and they will manage the claim on your behalf. Your statutory rights are unaffected.
- Please note that unauthorised trade reselling of RidgeMonkey products is prohibited. If you are an established high street retailer and wish to apply for a RidgeMonkey trade account, please contact Head Office on **+44 151 486 7070**
- All brand names and trademarks used in this instruction manual are property of their respective owners and in no way endorse (or imply endorsement) of any product described in this instruction manual.
- This instruction manual and all literature contained within remains copyright of RidgeMonkey®. Any unauthorised copying, lending or reproduction without prior written permission is strictly prohibited.



WWW.RIDGEMONKEY.CO.UK